



AMP UP THE WORKSPACE AMBIENCE WITH SPLENDID **BAJAJ LEVITARE**

Bajaj Levitare offers a range of captivating, thoughtfully designed illumination solutions. The product enhances the appeal of modern and smart workspaces and can be connected to a continuous rows of light.

PRODUCT SPECIFICATIONS

BAJAJ LEVITARE

Bajaj Levitare offers stellar lighting solutions to add a resplendent appeal in your work space. It is equipped with high performing capabilities such as proper suspension and wire kit. Given below are a plethora of the product's features:

Levitare features a mesmerizing appeal and offers both recessed and suspended applications. The product is marked with white powder coated finish extruded aluminium housing. It has a high performance diffuser that ensures commendable light transmission and pure effect. Carefully equipped with proper suspension and wire kit, it strictly complies with IS 10322 part 5/Sec 1 2012.

APPLICATIONS



WORKSTATIONS



MEETING ROOM



**BREAK OUT
AREA**



RECEPTION

TECHNICAL SPECIFICATIONS

Product Category	Technical Specification - Suspended / Surface (4ft)		
System Wattage	20W	28W	40W
Product Code	114029	114030	113992
Category Reference	BPCS 20W LED 4F D WH	BPCS 28W LED 4F D WH	BPCS 40W LED 4F D WH
Dimension in mm (L*W*H)	1200x55x80		
Lumen Flux	2200 lm	3000 lm	4400 lm
Luminaire Efficacy	110 lm/w		
CCT	5700k & 4000k		
CRI	>80		
Life	50,000 hrs.		
Operating Temperature Range	0°C to 45°C		
Input Voltage	140 to 270V AC		
PF	>0.95		
THD	<10%		
Built-in Surge Protection	4 KV		

Product Category	Technical Specification - Recessed (4ft)		
System Wattage	20W	28W	40W
Product Code	114063	114064	114065
Category Reference	BRCS 20W LED 4f D WH	BRCS 28W LED 4f D WH	BRCS 40W LED 4f D WH
Dimension in mm (L*W*H)	1200x55x35		
Lumen Flux	2200 lm	3000 lm	4400 lm
Luminaire Efficacy	110 lm/w		
CCT	5700k & 4000k		
CRI	>80		
Life	50,000 hrs.		
Operating Temperature Range	0°C to 45°C		
Input Voltage	140 to 270V AC		
PF	>0.95		
THD	<10%		
Built-in Surge Protection	4 KV		

TECHNICAL SPECIFICATIONS

Product Category	Technical Specification - Suspended / Surface (8ft)	
System Wattage	40W	56W
Product Code	On request	
Category Reference	BPCS 40W LED 8f D WH	BPCS 56W LED 8f D WH
Dimension in mm (L*W*H)	2400x55x80	1200x55x80
Lumen Flux	4400 lm	2400 lm
Luminaire Efficacy	110 lm/w	
CCT	5700k & 4000k	
CRI	>80	
Life	50,000 hrs.	
Operating Temperature Range	0°C to 45°C	
Input Voltage	140 to 270V AC	
PF	>0.95	
THD	<10%	
Built-in Surge Protection	4 KV	

Product Category	Technical Specification - Recessed (8ft)	
System Wattage	40W	56W
Product Code	On request	
Category Reference	BRCs 40W LED 8f D WH	BRCs 56W LED 8f D WH
Dimension in mm (L*W*H)	2400x55x35	
Lumen Flux	4400 lm	6160 lm
Luminaire Efficacy	110 lm/w	
CCT	5700k & 4000k	
CRI	>80	
Life	50,000 hrs.	
Operating Temperature Range	0°C to 45°C	
Input Voltage	140 to 270V AC	
PF	>0.95	
THD	<10%	
Built-in Surge Protection	4 KV	

*Images and visuals are for representation purpose only.