



## **HIGHLIGHT EVERY DETAIL**

Introducing Bajaj Glint COB Downlight  
for a perfectly illuminated ambience

Creating a stylish ambience, the new Bajaj Glint COB Downlight is housed in an aluminium die cast. It complies with IS 10322 part 5/Sec 1 2012 and is available in different wattages and CCT range. The high lumen LED has the best thermal management system that provides the better light output and has a longer service life. These adjustable luminaires are suitable for stand-alone and continuous installation in retail outlets, showrooms, office receptions, etc.

# Glint COB Downlight

## PRODUCT SPECIFICATIONS

TECHNICAL INFORMATION					
System Wattage	7w	12w	15w	18w	24w
Cut out	70mm	85 mm	85mm	115mm	125mm
Luminous Flux	595lm	1020lm	1275lm	1530lm	2040lm
Luminaire Efficacy	85 lm/W				
Correlated Colour Temperature	6500k/4000k & 3000k				
Colour Rendering Index	>80				
Operating Temperature Range	-10°C to 45°C				
Beam Angle ( $\pm 10\%$ )	36°				
Input Voltage	180 to 270V AC				
Power Factor	>0.95				
THD	<20%				
Built-in Surge Protection	4kV				

## APPLICATIONS



Office



Bank



Hospital



Cabins



Meeting room

\*Images and visuals are for representation purpose only.