

EASY TO USE. EASIER TO MAINTAIN.

Introducing high performance LED BATTEN for versatile commercial applications in office spaces, parkings, utility areas and all common areas.

General Information		
Product Category	LED Commercial Lighting	
System Wattage**	20W	
Luminaire Efficacy*	100 lm/W	
Correlated Color Temperature	6500K ±510K	
Color Rendering Index	>80	
Operating Temperature Range	-10°C to +45°C	

Product data and Ordering data			
Product Cat. Ref.	BCLAB 20W WH LED P	BCLAB 40W WH LED P	
Product Code	113978	113883	
Case Lot	20 Nos.	20 Nos.	
Net Weight	0.285 Kg. Approx.	0.285 Kg. Approx.	

Operating and Electrical			
Input Voltage range	180 to 270V AC	140 to 300V AC	
Input Frequency	50/60 Hz	50/60 Hz	
System Current in Amp.	@ 240V AC 0.08A	@ 240V AC 0.08A	
Power Factor	≥ 0.9	≥ 0.9	
Built-in Surge protection	3 kV	4 kV	

Approval	
Ingress Protection	IP20

APPLICATION AREAS



Areas





Office Spaces



Parking Spaces

^{*}Image used for representation purpose in the creative.





Areas



