# SKYLUX GLADDEN



R

Designed for optimal illumination of workstations.

ita

### **SKYLUX GLADDEN** Recess-Mounted Luminaires

Fully diffused Recess mounted contemporary workspace solution with white powder coating and CRCA front cover; Back lit luminaire with high efficiency and highly efficient diffuser provides for uniform illumination and better futuristic solution. Seamless and aesthetically well designed with uniform and optimum output which creates vibrant illumination and suitable for all kind of office applications.



#### Features

- CRCA white powder coated housing, having better aesthetic finish
- High lumen LEDs for better light output
- Comply with IS 10322 part 5/Sec 1 2012
- High performance diffuser for better light transmission and pure effect
- Suitable for Grid/Armstrong modular ceiling system

## Technical Specifications

SPECIFICATIONS	
Product Category	2x2 Recess mounted
System Wattage	36W
Luminous Flux	3600 lm
Luminaire Efficacy	100 lm/W
Correlated Colour Temperature	5700 K +/-300k
Colour Rendering Index	>80
Operating Temperature Range	-5°C to 50°C
Input Voltage	175 to 270V AC
Input frequency	50 Hz
THD	<20%
Power Factor	≥ 0.95
Built-in Surge protection	3 kV





## Application Areas





Cabins



Meeting rooms



Ordering info

ORDERING DETAILS		
Product Details	Item Code	Cat Ref
Floduct Details	113936	BZRSQL 36L LED GX
Case Lot	2 Nos.	
Net Weight	1.6 Kg Appx.	



/illumination@bajajelectricals.com /illumination.bajajelectricals.com f /BajajElecBiz /BajajElecBiz /BajajElecBiz in /BajajElectricals