



SINGLE / DOUBLE SIDED LED Signage

BESL 03 LED SSD WBB GREEN/RED

BESL 03 LED DSD WBB GREEN/RED



Cat. Ref.	Length	Width	Height
BESL 03 LED SSD WBB GREEN/RED	335	45	225
BESL 03 LED DSD WBB GREEN/RED	335	45	225

DIMENSIONS IN mm Tolerance +/-5

Application

- Commercial complexes,
- Showrooms, Airport lounges,
- Computer centers, Banks, Hospitals,
- Conference halls, Design offices, Control rooms, Laboratories, etc.

Specification

- Black painted Extruded aluminium housing.
- Green / Red LED's mounted inside the housing.
- Laser engraved Signage matter on Single / Double Acrylic sheet fixed on one side.
- In double sided version black paper is inserted.
- Ni-Cd Battery back up to 2 hrs. (Charged up to 8 - 10 Hrs)
- Mounting strings provided for pendent mounting
- Operating Voltage 150-280V AC
- Ambient operating temperature. – 0 to 45°C
- Ingress protection – IP42

Electrical Data

Product Code	Cat Ref	Mains Voltage (V)	LED Wattage (W)	System wattage (W)
220208	BESL 03 LED SSD WBB GREEN	240	3	8W
220209	BESL 03 LED SSD WBB RED	240	3	8W
220210	BESL 03 LED DSD WBB GREEN	240	3	8W
220211	BESL 03 LED DSD WBB RED	240	3	8W

Data subject to variation due to change/improvement in the design, materials and processes.

 BAJAJ LUMINAIRES <i>Making the difference</i>	DRAWN	KPM	20-06-2013	FOR – Std.
	CHECKED	SD		REV - 1 DATE-30-12-2013
	APPROVED	SC		DRG. No
	DATA SHEET RELEASED ON DT-			BESL 03 LED SSD/DSD-001
BAJAJ ELECTRICALS LIMITED 15/17, SANT SAVTA MARG, REAY ROAD, MUMBAI-400 010.				* E-mail : luminaires@bajajelectricals.com