



RETAIL LIGHTING

BXDR 30W WW / BXDR 30W WH



NOMINAL DIMENSIONS IN mm Tolerance +/-5

Applications

- Shopping malls,
- Retail show rooms, etc.

Specification

- White powder coated recess mounting pressure die-cast aluminium housing.
- Specially designed swivel type to adjust luminaire from 0° to 60° depending on lighting design need.
- Die-cast aluminium carriage assembly provided with heat sink for efficient dissipation of heat – important for LED luminaires.
- Lighting system comprising of COB LED & reflector : options available for Warm White (WW) and White (WH)
- Spring loaded mounting brackets to suit false ceiling – easy to install & maintain.
- Constant current output driver, operating range 150 – 275V AC supply voltages.
- Ingress protection – IP20

Electrical Data

Product Code	Cat. Ref.	Nominal Voltage (V)	System Wattage (W)	Mains Current in Milli Amps. At 240 V	Power Factor
112047	BXDR 30W WW	240	30W	145	0.95
112048	BXDR 30W WH	240	30W	145	0.95

Data subject to variation due to change/improvement in the design, materials and processes.

 BAJAJ LUMINAIRES <i>Making the difference</i>	DRAWN	KPM	30-10-2014	FOR –
	CHECKED	SD		REV - 0 DATE-30-10-2014
	APPROVED	SC		DRG.No
	DATA SHEET RELEASED ON DT-			BXDR 30W WW/WH - 001
BAJAJ ELECTRICALS LIMITED 15/17, SANT SAVTA MARG, REAY ROAD, MUMBAI-400 010.				* E-mail : luminaires@bajajelectricals.com