


LED INDUSTRIAL LIGHTING "DURANTO"

BGHB 200W LED GIV

200W LED Highbay Luminaire





NOMINAL DIMENSIONS IN mm Tolerance +/-5

Application

- · Airport hangers and warehouses, Heavy engineering industries,
- Thermal power stations, Railway concourse halls, Steel plants,
- Shopping malls, Departmental stores, Food plaza, etc.

Specification

- Powder coated high pressure die-cast aluminium LED housing.
- LED fixed on die-cast aluminum heat sink for proper thermal management.
- LED colour temperature: 5700K ±300K.
- Optics: Secondary lens optics provided.
- Constant voltage constant current SMPS, operating voltage range 100–300V AC, provided with open and short circuit protection and input surge voltage protection. (≥10kV)
- Eye-bolt provided for suspension mounting.
- Ingress Protection: IP65

Electrical Data

=										
Product	Cat. Ref.	Nominal	System	Mains Current	Power					
Code		Voltage	Wattage	in Amps.	Factor					
		(V) AC	(W)	At 240V AC						
169721	BGHB 200W LED GIV	240	200W	0.900	≥ 0.95					

Data subject to variation due to change/improvement in the design, materials and processes.

	DRAWN	KPM	10-04-2015	FOR -				
BAJAJ LUMINAIRES	CHECKED	SM		REV - 0	DATE-20-10-2015			
Making the difference	APPROVED	SC		DRG. No				
	DATA SHEET RELEASED ON DT-			BGHB 200W LED GIV - 01				
BAJAJ ELECTRICALS LIMITED 15/17. SANT SAVTA MARG. RFAY ROAD. MUMBAI-400 010. * F-mail: luminaires@bajajelectricals.com								